



**minipack**<sup>®</sup>  
THE ORIGINAL PIONEER

# TRAY SEALERS

E N G

Manual tray sealer - 200x270x100 mm

## DESCRIPTION

The **Sealpro 20** is a compact stainless steel table-top tray sealer. It's fitted with a thermoregulator for a precise setting of the sealing temperature and with a teflon coated sealing plate. It's the ideal machine for grocery stores and supermarkets.

The Sealpro 20 can be equipped with a double die in one piece which, with a simple extraction and rotation allows a simple and immediate tray size change.



## TECHNICAL FEATURES

Electrical power supply	V	220V 50hz
Maximum power installed	kW	1kW
Cycles/minute		Up to 5
Max tray size	mm	200x270x100
Max film reel width	mm	200
Double mould option		Yes
Customizable mould		Yes
Machine dimensions	mm	250x450x560
Weight (Net/Gross)	kg	30



## OPTIONAL

- Mould 1 tray
- Mould 2 trays
- Die-cut mold for each tray

Electric tray sealer - max tray dimensions 200x270x100 mm

## DESCRIPTION

The **Sealpro 20E**, a fully electric tray sealer of the latest generation, is the natural evolution of the established and reliable manual range.

The **Sealpro 20E** is entirely built in stainless steel and is equipped with a thermostat for accurate temperature regulation during sealing, as well as a preset welding time management system with different options to facilitate operator use.

It is the ideal machine for the delicatessen counter of shops and supermarkets.



## TECHNICAL FEATURES

Electrical power supply	V	220V 50hz
Maximum power installed	kW	1kW
Cycles/minute		up to 5
Max tray size	mm	200x270x100
Max film reel width	mm	200
Customizable stamp		Yes
Automatic welding and cutting		Yes
Dual safety sensor for mold insertion		Yes
Audible signal at the end of the cycle		Yes
Selectable preset welding time		Yes
Machine dimensions	mm	250x450x560
Weight	kg	30



## OPTIONAL

- Mold for 1 tray
- Mold for 2 trays
- Gas flushing version supplement
- Mold for 1 gas flushing tray
- Mold for 2 gas flushing trays
- Die-cut mold for each type of tray

Manual tray sealer - 340x270x100 mm

## DESCRIPTION

**Sealpro 25** is a stainless steel sturdy table-top tray sealer for big trays. It's fitted with a thermoregulator for a precise setting of the sealing temperature and with a teflon coated sealing plate. It can seal more trays per cycle according to their size.



## TECHNICAL FEATURES

Electrical power supply	V	230V 50hz
Maximum power installed	kW	1.5kW
Cycles/minute		Up to 5
Max tray size	mm	340x270x100
Max film reel width	mm	380
Customizable mould		Yes
Machine dimensions	mm	440x450x580
Weight (Net/Gross)	kg	45



## OPTIONAL

- Mould 1 tray
- Mould 2 trays
- Mould 3 trays
- Mould 4 trays
- Die-cut mold for each tray

Semi automatic tray sealer - max tray dimensions 380x270x120 mm

## DESCRIPTION

The **Sealpro 30** is a sturdy and reliable semi-automatic table-top tray sealer. The machine is extremely user-friendly and the quick mould change system allows a simple and rapid tray size change. The **Sealpro30** can be fitted with mould with profile cut for tray with different sizes and shapes.



## TECHNICAL FEATURES

Electrical power supply	V	230V 50hz
Maximum power installed	kW	2.5kW
Cycles/minute		up to 8
Max tray size	mm	380x270x120
Max film reel width	mm	420
Mould change		Yes
Customizable mould		Yes
Machine dimensions	mm	570x470x480
Weight	kg	40



## OPTIONAL

- Mold for 1 tray
- Mold for 2 trays
- Mold for 3 trays
- Mold for 4 trays
- Mold for 5 trays
- Mold for 6 trays
- Die-cut mold for each type of tray
- Universal sealing plate
- Gas flushing version supplement
- Die-cut mold for 1 gas flushing tray
- Die-cut mold for 2 gas flushing trays
- Silent compressor
- Stainless steel trolley

Electric tray sealer - max tray dimensions 385x270x100 mm

## DESCRIPTION

The **Sealpro 30E** is a sturdy and reliable fully electric semi-automatic table-top tray sealer. The machine is extremely user-friendly and the quick mould change system allows a simple and rapid tray size change. The **Sealpro 30E** can be fitted with mould with profile cut for tray with different sizes and shapes.



## TECHNICAL FEATURES

Electrical power supply	V	220V 50hz
Maximum power installed	kW	2kW
Cycles/minute		up to 10
Max tray size	mm	385x270x100
Max film reel width	mm	420
Customizable mould		Yes
Automatic sealing and cutting		Yes
Safety sensor for correct tool insertion		Yes
Cycle end light signal		Yes
Settable sealing temp. by Thermoregulator		Yes
Weight	kg	80
Machine dimensions	mm	570x470x480



## OPTIONAL

- Mold for 1 tray
- Mold for 2 trays
- Mold for 3 trays
- Mold for 4 trays
- Mold for 5 trays
- Mold for 6 trays
- Die-cut mold for each type of tray
- Universal sealing plate
- Gas flushing version supplement
- Die-cut mold for 1 gas flushing tray
- Die-cut mold for 2 gas flushing trays
- Stainless steel trolley

ATM tray sealer - max tray dimensions 380x270x120 mm

## DESCRIPTION

The **Sealpro 41** is a compact benchtop heat sealer for modified atmosphere packaging with particular attention to food hygiene and safety.

The vacuum sensor allows for precise adjustment of vacuum and gas levels. The drawer is mounted on special guides that enable effortless movement. Available in both die-cut mold and universal sealing plate versions.

The machine is extremely easy to use, even for operators without specific technical skills.



## TECHNICAL FEATURES

Power supply	V	230V 50hz
Maximum installed power	kW	1kW
Cycles per minute		up to 3
Maximum tray size	mm	265x180x90
Max roll width	mm	300
Vacuum pump	m <sup>3</sup> /h	8 (Busch)
Customizable mold		Yes
Modified atmosphere packaging (MAP)		Yes
Vacuum sensor		Yes
Machine dimensions	mm	380x640x670
Weight	kg	50



## OPTIONAL

- Mold for 1 tray
- Mold for 2 trays
- Universal sealing plate
- Skin mold on cardboard 2 imprints
- Die-cut mold for each tray

ATM tray sealer - max tray dimensions 380x270x120 mm

## DESCRIPTION

The **Sealpro 50 PLC** is the evolution of the Sealpro 50 heat sealer, equipped with a state-of-the-art multilingual PLC and a 4.3" color touchscreen panel.

In addition to the standard USB port which allows for program management and download of production programs, as well as the loading of any updates, it is also possible to request the installation of a photocell for printed film and a connection for remote assistance.

Like our entire range, the machine is extremely easy to use even for operators without specific technical skills.

Furthermore, the quick mold change system allows for format changes in just a few minutes and with minimal effort, thanks to special guides.



## TECHNICAL FEATURES

Power supply	V	230V-400V 50hz
Maximum installed power	kW	2.5kW
Cycles per minute		up to 5
Maximum tray size	mm	380x270x120
Max roll width	mm	420 (skin 450)
Vacuum pump	m <sup>3</sup> /h	20-40-60
Number of storable programs		100
Color touch screen		Yes
Customizable mold		Yes
Rapid mold change		Yes
Modified atmosphere packaging (MAP)		Yes
Vacuum sensor		Yes
Machine dimensions	mm	810x550x1350
Weight	kg	150



## OPTIONAL

- Touch screen PLC
- Printed film photocell
- Remote assistance kit
- Mold for 1 tray
- Mold for 2 trays
- Mold for 3 trays
- Mold for 4 trays
- Mold for 5 trays
- Mold for 6 trays
- Universal sealing plate
- Skin mold on cardboard 1 imprint (h. 45mm)
- Skin mold on cardboard 2 imprints (h. 45mm)
- Automatic trim winder standard or with rubberized roller
- Tray skin
- 10mm over skin on tray
- 40mm over skin on cardboard
- Automatic drawer opening closure
- Special voltage supplement
- Internal silent compressor



ATM tray sealer - max tray dimensions 380x270x120 mm

## DESCRIPTION

La **Sealpro 50** è stata progettata per il confezionamento in atmosfera modificata, ponendo particolare attenzione all'igiene alimentare e alla sicurezza.

Grazie all'installazione di un sensore apposito, consente una regolazione precisa del vuoto e del gas, rendendola adatta anche per operatori senza esperienza tecnica. Inoltre, il sistema di cambio stampo rapido consente di cambiare il formato in pochi minuti, mentre il cassetto, montato su guide speciali, si muove agevolmente.



## TECHNICAL FEATURES

Power supply	V	230V-400V 50hz
Maximum installed power	kW	2.5kW
Cycles per minute		up to 5
Maximum tray size	mm	380x270x120
Max roll width	mm	420 (skin 450)
Mold change		Yes
Customizable mold		Yes
Vacuum pump	m <sup>3</sup> /h	20-40-60
Modified atmosphere packaging (MAP)		Yes
Vacuum sensor		Yes
Customized digital sealing programs		Yes
Machine dimensions	mm	810x550x1300
Weight	kg	150



## OPTIONAL

- Mold for 1 tray
- Mold for 2 trays
- Mold for 3 trays
- Mold for 4 trays
- Mold for 5 trays
- Mold for 6 trays
- Universal sealing plate
- Skin mold on cardboard 1 imprint (h. 45mm)
- Skin mold on cardboard 2 imprints (h. 45mm)
- Automatic trim winder standard or with rubberized roller
- Tray skin
- 10mm over skin on tray
- 40mm over skin on cardboard
- Automatic drawer opening closure
- Special voltage supplement
- Internal silent compressor