

MEDIA MATIC



MEDIA MATIC: an efficient and versatile monoblock shrink-wrapping machine

MEDIA MATIC represents the latest addition by **minipack®-torre** to the range of modular semi-automatic **L-sealers**, featuring a monoblock structure that sets it apart from the other solutions. Specifically, the shrink tunnel — equipped with a system for adjusting packaging speed, height and temperature — is fully integrated into the sealing unit, making the machine structure versatile and compact.


MEDIA MATIC features an outstanding series of high-level technical solutions, including electronic sealing-time adjustment and Teflon-coated blades, which ensure the complete absence of fumes. At the same time, this L-sealer comes with a complete standard “equipment” package: motorised sealing bar and scrap winder included.

In short, **MEDIA MATIC** is the perfect packaging machine for all companies that think big!

Technical data

Power supply	208V 60Hz 3Ph 230V 50Hz 3Ph 400V 50Hz 3Ph 400V 50/60Hz 3Ph
Maximum installed power	6,5 kW (208V) 6,3 A (230V) 6,3 A (400V) 6,3 A (400V)
Maximum electrical absorption	19 A (208V) 17 A (230V) 10 A (400V) 10 A (400V)
Hourly production (variable depending on the type of film and the size of the product)	0-750 p/h
Maximum roll dimensions	Ø350x600 mm
Mass dimensions of the product (the measurement of mass cannot be ottenute contemporaneously)	500x360x200 mm
Worktop height	875 mm
Machine dimensions (sealing frame open)	2780x730x1400 mm
Machine dimensions (sealing frame closed)	2780x730x1400 mm
Machine weight (net/gross)	287/343 kg

Optional



Double-roller conveyor belt kit Media Matic

NT400001

Compared with the standard version, this conveyor belt features twice the number of rollers, reducing the gap between adjacent rollers. This configuration improves the handling of small products, preventing them from becoming trapped or falling between the rollers. The result is smoother product flow, greater product stability and improved continuity throughout the packaging process.



Foot pedal kit FM76A/FM77A evo-A - Replay 55C - Modular 50S/70 - Media Matic

S0800001

The foot switch is particularly used on machines where the production process requires the operator to use both hands. The pedal allows the operator to START and STOP the machine with their foot, without assistance from other people.