

MODULAR 70



Modular 70: the flexible, easy-to-use shrink wrapping machine

The **MODULAR** line includes a range of semi-automatic **L-sealers** designed to meet the sector's requirements for flexibility and quality, offering products with an excellent price-performance ratio.

If you are looking for **L-sealers** that deliver outstanding pack appearance, **MODULAR 50S** and **MODULAR 70** are the ideal machines for your needs, packaging with any material accurately and with excellent aesthetic results.

MODULAR LINE uses an electronically controlled sealing system and a series of extremely advanced safety devices. The possibility of using the lines in automatic or semi-automatic mode, together with customizable operating programs, simplifies every packaging stage and significantly increases production output.

MODULAR 50S and **MODULAR 70** can be completed with the **TUNNEL** line by minipack®-torre.

TECHNICAL FEATURES:


- Teflon-coated sealing blade
- Double sealing bar with shock absorber
- Continuous-cycle cooling system
- Manual or automatic mode

- Adjustable work surface
- Motorized belt with adjustable speed
- Integrated film-roll support
- Digital panel with 6 programs
- Piece counter
- Delayed bar opening for seal cooling
- Emergency switch.

Technical data

Power supply	200V 50/60Hz 3Ph 208/220V 60Hz 3Ph 230V 50Hz 3Ph 400V 50Hz 3Ph
Maximum installed power	2,5 kW
Maximum electrical absorption	12,5 A (200V) 12 A (208V); 11,3 A (220V) 10,8 A (230V) 6,3 A (400V)
Hourly production (variable depending on the type of film and the size of the product)	0-900 p/h
Maximum roll dimensions	Ø300x800 mm
Mass dimensions of the product (the measurement of mass cannot be ottenute contemporaneously)	800x550x200 mm
Worktop height	930 mm
Machine dimensions (sealing frame open)	2070x960x1510 mm
Machine dimensions (sealing frame closed)	2070x960x1220 mm
Machine weight (net/gross)	243/290 kg

Optional



Micro-perforator kit with counter plate
Modular 70

KR130001

This optional ensures more regular and precise micro-perforation. It is particularly suitable for customers looking for an excellent aesthetic result. A more regular hole during the shrink-wrapping phase



Foot pedal kit FM76A/FM77A evo-A -
Replay 55C - Modular 50S/70 - Media
Matic

S0800001

The foot switch is particularly used on machines where the production process requires the operator to use both hands. The pedal allows the operator to START and



improves the final appearance.

STOP the machine with their foot, without assistance from other people.
